



J.D. Irving, Limited
PURCHASE WOOD SPECIFICATIONS

SUSSEX CHIP PLANT – SOFTWOOD PULPWOOD

EFFECTIVE DATE: May 14th, 2017 weight scale

GRADE 0 Spruce-Fir-Jack Pine Pulpwood (SF PW)	
SPECIES	Spruce/fir/jack pine mix (no limit on fir or jack pine content). May contain up to 5% (maximum) white pine and/or tamarack (i.e., eastern larch) content. NO hemlock or red pine content.
AGE	Delivered within 6 months of date cut
LENGTH	8-foot or 9-foot: 96” to 114”. Loads of 9-foot may contain up to 20% 8-foot pieces.
DIAMETER	3.5” (inside bark) minimum to 20” maximum
DEFECTS	Not more than 5% rot per load. Individual pieces cannot have more than 50% total deductions for rot and/or defects.
	No forked or excessively crooked pieces. Bolts must be able to pass through the 20” diameter chipper infeed (i.e., like going through a 20” culvert pipe).
GRADE 4 White Pine or Tamarack Pulpwood (WP PW, TA PW)	
SPECIES	Loads of softwood pulpwood with greater than 5% White Pine or Tamarack content but NO hemlock or red pine.
	All other specifications are as above

Defective bolts may be rejected and loaded back on truck. Any disputes regarding scale must be brought to the attention of JDI scale staff at the time of delivery by the trucker or producer. These specifications are subject to change by J.D. Irving, Limited with minimum notice.

Signed: 
Brent Thompson

Date: April 20th, 2017